

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland
tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu



Application

Designed especially for protection of vans and trucks. Applied also in community buildings, office rooms, production facilities, storerooms, garages.



Basic features

- Easy and ergonomic operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



Technical data

Extinguishing efficiency	13A 89B C
Weight of extinguishing agent	2 kg
Working agent	N ₂
Operation time	min. 9 s
Cylinder test pressure	27 bar
Operation pressure	12 bar
Operating temperature	-30 °C/+60 °C
Total weight	~3,5 kg
Fire under voltage	1000 V
Total height (A)	345 mm
Cylinder diameter (B)	110 mm



Powder extinguisher GP-2x ABC